



1.8m CJ1000 Series Solvent Printer

Item Code: LFIP-JH-CJ1000



FOB Price: **\$7,550/set**

Mini Order: 1 set

Shipping Weight: ★★☆☆☆

Average Rating: 484.0lb (220kg)

[Inquire Now](#)

Overview

Description:

The LFIP-JH-CJ1000 series inkjet printers are designed to make up the disadvantages from `indoor` and outdoor inkjet printers which are low speed and low resolution. These specific printers are practical and widely demanded.

Image not found
/userfiles/2011-Sep/111(1).jpg



Characteristics:

- . Uses Eco- solvent ink.
- . Smallest droplet is 12PL. It is next to indoor printers, but the cost is much better than it.
- . Constant pressure ink supplying, constant level in ink cartridges and unique screw adjustment make liquid level adjustment accuracy in 1mm.
- . One pole and roller feed system solve wrong position of media. It adopts media preheating, printing panel heating and drying after printing three section heating mode, then improve printing of PVC materials.
- . Providing 47.2"*94.5" (1200*2400mm) sheet printing frame could be used for printing on boards in high precision.
- . AIO human emergence control platform includes automatically jumping blank, correcting step in printing, two-ways parameters, automatically copies a single figure, make-up, wave eclosion and linear eclosion function.

Application:

Stop sign light boxes, display panels PS board, car advertising, wallpaper printing

Details

Colors	KCMY/KCMYLCLM
Print Speed	240X540 3pass 20m ² /hr
Maximum Resolution	1440dpi
Max Media Width	70.8" (1800mm)
Ink type	Solvent Inks
Print head	SPT255_12PL printhead
Max print width	69.7" (1770 mm)

Specifications

Model	CJ1806	CJ1804	CJ1803
Printhead	SPT255_12PL	SPT255_35PL	SPT510_2C Double
No of Printheads	6	4	3
Printhead combination	1x6	1X4	2cx3
Print Width	69.7" (1770 mm)		
Media Width	70.8" (1800mm)		
Media Applicable	PVC Vinyl Sticker, Flex banner, Sheet material,solvent outdoor		
Print speed	Print mode	Speed	Speed
	High speed	360X1080 6pass 12.6m ² /hr	360X1080 6pass 10m ² /hr
	Middle speed	360X1440 8pass 9.5m ² /hr	360X1440 8pass 7m ² /hr
	Standard speed	720X1080 6pass 6.8m ² /hr	720X1080 6pass 4m ² /hr
Ink Type	Ink Type	Eco Solvent Ink	
	Color	KCMYLcLm?	KCMY
Media Type	PVC Vinyl Sticker, Flex banner, Sheet material, Solvent outdoor medias etc.		
Ink supply system	Constant-pressure ink supply		
Cleaning method	Positive flush, Auto flushing & Head moisturizing		
RIP software	MainTop(Photoprint optional)		MainTop(Photoprint
Interface	USB2.0		

Printing assistant system	Auto feeding & take up system	Infrared detecting, feeding & take-up system with memory function
	Heating system	Media Heating on Front,middle and rear
	Head heating	Low voltage head consistent-temperature heating
	Height of the tray	0.1"~0.4"(2~10mm) Distance to platform, adjustable
	Sheet material printing	Independent external bracket for flatbed printing (size for sheet material:max thickness 0.2" (5mm), material should be equipped with non-slip bottom)
	Other functions	One key positive-pressure ink injecting, adjustable force of media being absopcted to platform, anti-warper heater,lighting for head cleaning,anti-splash board.
Printer info	Operating voltage	AC220V 50/60HZ (AC110V 50/60HZ is optional)
	Power	Printing system :500W Heating system(Post-,600w, print-,600w, pre-, 600w)
	Working Environment	Normal temperature: 22~28? Himidity: 40%~70%RH
	Printer dimensins	106.7"×32.3"×45.7" (2710×820×1160mm) 7.1*0.6lb (180±15kg)
	Shipping dimensins	110.0"×26.8"×27.6" (2790×680×700mm) 8.7*0.6lb (220±15kg)



Copyright © 1999-2012 by Beijing ChinaSigns Information Company Limited All Rights Reserved.

Email:info@sign-in-china.com Tel:+86 132 6410 3286 www.sign-in-china.com