

380mm(15") Fast Heating-up Desktop Multi-function Hot Laminator

Item Code: FMJ-380-RW



Overview

FMJ-380-RW: 380mm (15") Desktop MULTI-FUNCTION HOT Laminator

Fast Heating-up.

It can conduct mounting and hot lamination with a single side or double side lamination for multiple deployment choices is available. The hot laminator is the initial choice after the printing process, and one of the perfect equipment's for all kinds of post-production printing.

Product Highlights:

Maximum working film width 15".

With a unique design and surface plastic spay treatment.

Simple construction, good operability, safe, complete and reliable functions.

The hot laminator can be used to laminate printed materials, important documentation, engineering drawings, photographs, and more; it also can be used in cold lamination for wedding photographs and other important events.

It can use rolling material to process the objectives and also to make overlay film on independently surface objectives.

Application:

This multi-function hot laminator can be used to laminate printed materials, important documentation, engineering drawings, photographs, and more; it also can be used in cold lamination for wedding photographs and other important events.

Applicable Laminating Medium:

Photopaper, PP, self-adhesive PP, backlit film or transparent film.

Warranty and after sales services:

One year of warranty except the spare parts.

24 hours technical support by mail or phone.

User friendly English manual on how to use the machine and accomplish the maintenance.

Details

Maximum Laminating Width	15" (380mm)
Maximum Laminating Thickness	0.3" (8mm)
Rollers Diameter	1.5" (38mm)
Maximum Laminating Speed	39" (1m) / min
Maximum Internal Diameter of	1", 3" (2.25" Optional)
Profile	With functions of double sided hot laminating, single
sided hot laminating, single sided cold laminating, cold	

Specifications

and hot mounting, mounting and encapsulating.

Model	Plastics shell, small size hot laminator, easy to FMJ-380-RW transport and operation.
Max. laminating width	380mm(15")
Max. laminating thickness	8mm (0.3")
Film thickness	30-125mm(1.2"-5")
Temperature adjustment range	80-150 degree
Speed range	1m (40"/min)/min
Media core size	1"- 3"
Power supply	AC 80V-110V 110V-240V; 50Hz or 60Hz
Machine dimension	23.6" x 16.1" x 15.4" (599 x 409 x 390mm)
Machine weight	56.4Lb (25.6kg)
Package	Fumigation free package
Packing size	26.0" x 20.9" x 19.3" (660 x 530 x 490mm)
Gross weight	68.3Lb (31kg)



Copyright © 1999-2012 by Beijing ChinaSigns Information Company Limited All Rights Reserved.

Email:info@sign-in-china.com Tel:+86 132 6410 3286 www.sign-in-china.com