



2-SMD 3528 Non water-proof module 26x7mm

Item Code: LED module-LBY-3F12T2607-2CNWF



FOB Price: **\$0.33/pc**

Mini Order: 200 pcs

Average Rating: 1b (kg)

[Inquire Now](#)

Overview

Characteristics:

- . High brightness LED SMD as a lamp-house, with wide angle view and a small aperture.
- . Controlled by the chips with constant current, has a steady current between the cathode and the anode.
- . Low voltage, safe and jarless.
- . With a settled orifice and 3M gummed paper, very convenient to install.
- . Longlife above 80,000hrs.
- . Low power consumption, energy conservation and made for save electricity.

Usage:

LED SMD modules are widely used for solid lighting character, LED signs, LED lighting box, scenery designs and decoration, etc.

Sample:**Details**

LED Number	2
SMD Package Model	3528
Color	White
Shape	Rectangular
Brightness	Low
Material	Plastic

Specifications

Basic parameter			
	Red, yellow, blue, green and white		
Color	2PCS	LED type	3528 SMD6
LED Quantity	Gray 0.5mm 0.1"*3.0"	Diemensions	1.0"*0.3" (26*7mm)
Module interface	(2*75mm) RVleads	Interface definition	Gray anode,white cathode

Cluster quantity

20pcs

Space between modules

Weight	0.4oz (10g)±5%	Lifetime	MTBF>50000hours
Environment parameters			
Working temperature	-40°C?60°C		
Outdoor level	IP68 completely satisfies the outdoor lighting		
Electronic specification			
Input voltage	D12V±5%	Max power	0.15 W
Driving mode	Invariablenes Voltage! (Insure every LED working under the invariablenes voltage)		
lighting capability			
Luminous flux	0.4f1oz (12lm)		
Beam angle	160°-180°		



NETSUITE®
ONE SYSTEM. NO LIMITS.



Copyright © 1999-2012 by Beijing ChinaSigns Information Company Limited All Rights Reserved.

Email:info@sign-in-china.com Tel:+86 132 6410 3286 www.sign-in-china.com