3.2M WD Series Solvent Pirnter(XAAR600-60PL)

Item Code: LFIP-MJT-WD3216XR60

FOB Price:	**$30,769/set**
Mini Order:	1 set
Shipping Weight:	★★★★☆
Average Rating:	3700.4lb (1682kg)

Inquire Now

Overview

Description:
Uses Xaar 600 particle printhead, the advanced piezoelectric crystal alloy increasing the print speed up to 60%. Exclusive internal automatic temperature compensation function.
.4/8/12/16 heats, can upgrade freely.
.The carriage height can be easily adjusted.
.Automatic ink cup printhead protection device.

Linear guide rails with double-slider and sound off function.
Features a simple construction, with low static sliding friction factor, satisfactory firmness, good loading capacity, steady transmission and high precision assurance.

High-power double AC servo system; long life time, high precision and fast response, is the foundation of stable work of the printer. With a fast and excellent after sales global service.

French Schneider Electric Switch
Up to IEC,UL,CSA standard, with CE certificate. The safety grade is IP65, adopts patent "Protected LED" Luminescence Instruction Cell and screw junction. It can also be used on the stylus junction of printing circuit.

PALL capsule-type filter from USA
Adopts foldaway technology made from `importing` filter membrane; it has a big filter area, high speed filter capability and long work life, suitable for big volume of liquid filtering. With high filtering capability, prolongs the work life of the printhead, decreasing the waste of ink and the trouble time reduces the total cost of filtering.
. Separate ink pressure system, saving ink and decreasing the cost of the clients.
. Ink temperature system.
. Photoelectricity sensor and automatic correction system.
. Three-heating system: Pre-heater, printer heater, and after heater, adjust the temperature of the media, increasing the printing quality.
. Convenient printing platform light to view the printing and the printhead status.
. External monitor mounting bracket with hidden keyboard tray.

Package Size: 187.4"x37.4"x53.1" (4760x950x1350mm)
Net Weight/Gross Weight: 1874.0lb (850kg)/2094.4lb (950kg)

Details:

Details

Colors	C,M,Y,K
Print Speed	Maximum:240×360dpi:120?/h 2pass
Maximum Resolution	720dpi
Max Media Width	126.0" (3200mm)
Ink type	Solvent Inks
Print head	Xaar 600 Particle Printhead
Max print width	126.0" (3200mm)

Specifications

Model	WD3216XR60
Printing Type	Separation Printing
Printing Technology	Piezo printing (16 printheads)
Printhead Type	Xaar 600 Particle Printhead
Media Transmission	Roll to Roll
Printing Port	High speed USB boards
Data Transmission	Fabric Cable
Output Model	Rip Printing/Printing After RIP/Net-print
RIP Software	Photoprint,Ultraprint
Printing Mode	4 Colors with 12 printheads

Speed	High speed:	240*360dpi:120m2/h 2pass
	Mid speed:	240*540dpi:90m2/h 3pass
	Low speed:	360*720dpi:50m2/h 4pass
Heating System		Four Heaters: front heater, bed heater, rear heater, printhead heater
Cleaning System		Air Pressure and Suction Cleaning
Frame Structure		Steady steel structure is used on the machine body, and the combination of aluminum and steel on the girder
Color		C,M,Y,K
Power Requirement		220V AC
System		220V±10%,<4A,50/60HZ
Heating		220V±10%,<16A,50/60HZ
Operation Environment		Temperature:20°C?25°C ;Humidity:40%?70%RH
Printing Resolution		Adjustable(From 240dpi,360dpi to 1440dpi)
Media Types		Banner, adhesive vinyl, PVC self adhesive, backlit, flex media within 5mm thickness
Printing/Media Width		71.0" (1800mm), 98.4" (2500mm),126.0" (3200mm)