


Coated Backlit Flex Banner(Matte)

Item Code: BS-CB005-GL-2-M



FOB Price: **\$2.45/sq.m**

Mini Order: 40 rolls

Average Rating: Ib (kg)

Inquire Now

Overview

Product Characteristic:

- . 32% above high light-admitting quality.
- . Anti-UV, weather-resistant.
- . Mildewproof, antifouling processed surface.
- . Could be printed directly or with the film.
- . Strong structure, anti-typhoon.
- . Flame retardant, safe.
- . Bearing chemistry solvent.

Product Description:

Good smoothness, high bonding strength, stable ink absorbing, expressive force, self-cleaning, faster drying, perfect printing ability, anti-UV surface.

Application:

Signage, digital printing, screen printing for banner and outdoor, indoor digital printing and so on.





Details

Length	164.0 ft(50m)
Width	3.3-10.5 ft(1-3.2m)
Speci-	1000*1000 20*20
Thickness	610

Specifications

Item		Metric		Test Method	
Weight	510±10	gsm	DIN53352 BS342	24	
Breaking Strength	2100/1850	N/2.0" (5cm)	DIN53354 BS342	24	
Tearing Strength	300/250	N	DIN53356 BS342	24	
Adhesion	80	N/2.0" (5cm)	DIN53357 BS342	24	
Width	Up to 11.5' (350cm) (1010)				
FR Certification	We can reach:M2,B1,B2,DIN75200,NFPA701				
Lacquering	Products can be lacquered with ACRYLIC or PVDF				
Cd%,Pb%,As%,Ba%,Cr%,Hg%,Se%	We can reach:EN71-3				





















Copyright © 1999-2012 by Beijing ChinaSigns Information Company Limited All Rights Reserved.