



Flexible Steel Media

Item Code: MC-FF-UV-T290



FOB Price: **\$6.87/sq.m**

Mini Order: 1 roll

Average Rating: lb (kg)

[Inquire Now](#)

Overview

Description:

This steel film is a flexible and printable magnetic receptive material. It's not magnet but can be easily placed on magnetic boards. This easy-to-change and long term durable film has good holding power and stability, making it perfect for indoor and outdoor POP when you use magnetic boards together.

If you use the steel film and the flexible magnet together to make up a Rapid Display POP System, it will give you an innovative, standard, unified and simple POP way.

Application:

- . Easy-to-install, Easy-to-change, removable, reusable, uses for general signage and other flat-surface/ curved-surface, medium-term, indoor or outdoor applications such as:
- . Point of purchase display/Commercial Signage in Super Market, Retail/Grocery Shops, and Restaurant...
- . Removable/Changeable advertisements in subway, railway station, Business Center
- . Business wall outside
- . Map Guide in exhibition center, road side
- . Kids Wall in House




1




2



3



4



5

1200* 6000mm, 40 Seconds

Details

Characteristics	with steel powder in material
Mainly used for	common display printing
Code	MC-FF-UV-T290
Surface	PET
Finish	Semi-gloss (waterproof)
Substrate	Steel
GSM	290g/sq.m
Thickness	0.006"(0.15mm)
Available Length	393.7"/787.4"/1181.1"(10000mm/20000mm/30000mm)
Available Width	45.7"/49.6"(1160mm/1260mm)
Shelf Life	2 Year
Printing Method	Screen Printing,UV Printing
Temperature range after	4? to 158?(-20°C to +70°C)

application

Specifications

		MC-FF-9000SOL-T310	MC-FP-ART310	MC-FP-2GLO340	MC-FP-2JET250
Steel Film	MC-FF-UV-T290	9000SOL-T310	MC-FP-ART310	MC-FP-2GLO340	MC-FP-2JET250
Surface	PET, white, opaque	PET, white, opaque	3.8oz (108g) Paper, white	Copper print Paper, white	Copper print Paper, white
Substrate	Semi-gloss (waterproof),	Gloss (waterproof),	Matt (non-waterproof),	Gloss (non-waterproof),	Semi-gloss (non-waterproof),
Finish	Antifust	Antifust	Antifust	Antifust	Antifust
GSM	290g/m2	310g/m2	310g/m2	340g/m2	250g/m2
Thickness	0.15mm	0.17mm	0.18mm	0.18mm	0.15mm
Available Length	32.8'/65.6'/98.4' (10m/ 20m/ 30m)				
Available Width	45.7" (1160mm)/ 49.6" (1260mm)	45.7" (1160mm)/ 49.6" (1260mm)	40.6" (1030mm)	40.6" (1030mm)	40.6" (1030mm)
Shelf Life	2 Year				
Application	POP/ Exhibit; Outdoor	POP/ Exhibit; Outdoor	Children's Book; Sports Book; Postcard	DIY PHOTO;	DIY PHOTO;
Printing Method recommendation	UV Printing, Screen Printing, Promotional	UV Printing, Inkjet Printing, Promotional			

Inks	UV Curable Ink	UV Curable Ink, Solvent & Eco- Solvent Ink			
	MIMAKI: JF-1610	Roland: SOLJET PROIII YJ-640 Roland: VERSA CMM VP-300		Dye, Pigment	Dye, Pigment
	HP Scitex: TJ 8300/8500	Roland: II- FIJET PRO III FJ-740			
		HP: 8000s/9000s/ 10000s			
		MIMAKI: JV3- 75SP/ 130SP/ 160SP/ 250SP Mutoh: JVS 130S/ 160S			
Temperature range after application	-20°C to +70°C	-20°C to +70°C	-20°C to +70°C	-20°C to +70°C	-20°C to +70°C

Recommended Printers

Heidelberg

Desktop
Printers:
CANON, HP,
Espon

Desktop
Printers:
CANON, HP,
Espon



Copyright © 1999-2012 by Beijing ChinaSigns Information Company Limited All Rights Reserved.

Email: info@sign-in-china.com Tel: +86 132 6410 3286 www.sign-in-china.com