

Laminated Frontlit Flex Banner

Item Code: BS-LF009-GL-G



FOB Price: \$0.98/sq.m

Mini Order: 40 rolls


Average Rating: Ib (kg)

Inquire Now

Overview

Product Characteristic:

- . Completely light tight.
- . Anti-UV, weather-resistant.
- . Mildewproof, antifouling processed surface.
- . Could be printed directly or with the film.
- . Strong structure, anti-typhoon.
- . Flame retardant, safe.



. Bearing chemistry solvent.

Product Description:

Good smoothness, high bonding strength, stable ink absorbing, expressive force, self-cleaning, faster drying, perfect printing ability, anti-UV surface.

Packing:

Inner cores are packed with craft paper or hard tube.

Signage, digital printing, screen printing for banner and outdoor, indoor digital printing and so on.

Details

Speci-	300*500 18*12
Width	3.3-10.5 ft(1-3.2m)
Length	164.0 ft(50m)
Thickness	440

Specifications

ltem		Metric	Test Method	
Weight	440±10	gsm	DIN53352 BS3424	
Breaking Strength	635/451	N/2.0" (5cm)	DIN53354 BS3424	
Tearing Strength	125/107	N	DIN53356 BS3424	
Adhesion	60	N/2.0" (5cm)	DIN53357 BS3424	
Width	Up to 11.5' (350cm) (0305)			
FR Certification	We can reach:M2,B1,B2,DIN75200,NFPA701			
Lacquering	Products can be lacquered with ACRYLIC or PVDF			
Cd%,Pb%,As%,Ba%,Cr%,Hg%,Se%	We can reach:EN71-3			





















Copyright © 1999-2012 by Beijing ChinaSigns Information Company Limited All Rights Reserved.

Email:info@sign-in-china.com Tel:+86 132 6410 3286 www.sign-in-china.com