



P20 outdoor Tricolor LED messageboard

Item Code: TCMB-LJ-P20outdoor



FOB Price: **\$818/sq.m**

Mini Order: 1 roll

Average Rating: lb (kg)

[Inquire Now](#)

Overview

The Tri-Color LED Screen is widely used for indoor and outdoor display messaging, outdoor AD sign display and much more. Features a wide range angle and distance view, uniform illumination and excellent brightness. There is a low rate of failures; the LED screen has a long lifespan, low consumption of energy and excellent performance.

Application:

This Tri-Color LED Screen is designed for outdoor information, AD sign display and other outdoor uses.

Specifications

Specification:

Pixel pitch	0.8" (20m)
Pixel configuration	2R 1G
Pixel Density	2500dots/?

Ideal viewing distance	29.5'-85.3' (9m-26m)
Ideal viewing angle	160°
Control method	Synchronization/ Asynchronization
Driving method	Constant 1/4 scanning
Frame frequency	?60HZ
Refresh frequency	?180HZ
Max. power	<300W
Brightness	?5000cd/?
IP grade	IP65 front, IP54 back
Voltage range	AC220v/110±10%
Ideal temperature	-10??+45?
MTBF	More than 10,000 hours
Lifespan	10,000 hours



Copyright © 1999-2012 by Beijing ChinaSigns Information Company Limited All Rights Reserved.

Email:info@sign-in-china.com Tel:+86 132 6410 3286 www.sign-in-china.com