



Composite panels are used in most buildings for the cladding of building exterior. They have excellent resistance to fire, impact, corrosion, and weathering. They are also easy to install and maintain.

om
signs

Composite Panel(Natural)

01

FOB Price: **\$46.81/sq.m**

Mini Order: 900 rolls

Average Rating: 1b (kg)

[Inquire Now](#)

Overview

Product specification list				
Specification	Panel total thickness	Metal skin thickness(mm)	Width	Length
specifi-01	0.1" (3mm)	0.10/0.10	23.6" (600mm)	Standard:126.0" (3200mm) Customization available
specifi-02	0.2" (4mm)	0.20/0.20	38.6" (980mm)	
specifi-03	0.2" (4mm)	0.30/0.30	43.3" (1100mm)	

Characteristics for SSPP:				
Test Item	Unit	Perfomation indicators		
		3(4)*0.30/0.30mm	3(4)*0.20/0.20mm	3(4)*0.10/0.10mm
180°Peel-off Strength	N·/mm/mm	≥130	≥130	≥130
Unit Weight	kg/m2	7.0±0.5(8.0±0.5)	5.6±0.5(6.5±0.5)	4.1±0.5(5.0±0.5)
Flexural Strength	Mpa	≥130	≥125	≥70
Flexural Modulus	10/m4Mpa	≥3.5	≥3.2	≥2.5
Penetrating Resistance	kN	≥20	≥15	≥8.0
Shear Strength	MPa	≥68	≥58	≥30