LED Exposure Machine Product Introduction

LED exposure unit is used in the filed of plate-making such as pad plate, screen plate, hot stamper plate, resin plate. when you put the film onto the plate into UV LED exposure machine, start it, the emulsion on the plate will appear a unseen imagine. this is important process on all plate-making technology.

Parameter

Max.exposing area(mm):520mmx610mm

Voltage (single phase): 110V~220V

Time control: 0-999s

Power of lamps: 80W (8 10w UV LED-line)

Exposure time:40~70 seconds

Net Weight: 30KG

Packing size: in one canon(750*680*200mm)

Feature

Adopting high efficiency UV LED light source, which save 50% electricity than ordinary model.

PLC controlled panel, very easy to operate.

Automatic memory function for working as original seating next time

Perfect exposure effect because of LED light.

Fast exposure time, about 40-70 seconds.

Energy saving and environment friendly.

Stable exposure quality, more lifetime.

Durable and beautiful with steel coat.

Outside connecting power plug, safety and convenience.

Easy to transport, LED light is not fragile in delivery.





Control panel operation:

- 1. Exposure setting time: Click "EXPOSURE" The red indicator light is on, adjust "+" "-" to set the pumping time, the display will show the blue digital time, it is recommended to be $10^{\sim}60$ seconds.
- 2. "REST" button use: Click "REST" time during the set time to start from 0
- 3. Press the "START" button to start the work, press the pause again, press again to continue working.

